



Flexi unit

Features

The stylish Flexi unit brings a touch of luxury to light commercial interiors. It incorporates the latest Toshiba technology, and meets the needs of all occupants.

Installation flexibility and indoor air quality are two of the many advantages of the system.

Key features

Ultimate flexibility: choice of low-wall or ceiling-suspended installation, without any need for modifications or additional accessories.

Triple-action filtering system first removes large particles. Then a passive electrostatic filter removes solid particles down to 0.01 micron in size and finally the Zeolite Plus filter absorbs even smaller airborne pollutants.

Natural air distribution: in ceiling-suspended applications air can be directed either horizontally, parallel to the ceiling or far away from the room occupants, for non-intrusive air distribution.

High-lift drain pump kit: raises drain piping up to 290 mm for flexible condensate piping layout (option - suitable for ceiling-suspended unit only).

R-410A HEAT PUMPS

CEILING-SUSPENDED/LOW-WALL UNIT

Triple-action filtering system

Zeolite Plus filter

Technical specifications heat pump

Indoor unit Outdoor unit		SM562XT-E SM56_AT-E	SM802XT-E SM80_AT-E
		2 HP	3 HP
Cooling capacity (min. - nom. - max.)	kW	1.5 - 5.0 - 5.6	1.5 - 6.7 - 7.0
EER	W/W	2.67	2.46
Heating capacity (min. - nom. - max.)	kW	1.5 - 5.6 - 6.3	1.5 - 8.0 - 9.0
COP	W/W	3.29	3.00
Energy efficiency class, cooling/heating		D/C	E/D
Sound pressure level (h/l)	dB(A)	43/36	46/37
Sound power level (h/l)	dB(A)	58/51	61/52
Dimensions (H x L x D)	mm	208 x 1093 x 633	208 x 1093 x 633
Weight	kg	23	23