



High-wall unit

Features

With the Light Commercial high-wall inverter unit, Toshiba offers an attractive and slimline design for offices, restaurants and other applications where a light, compact and elegant solution is needed.

Moreover the latest filters designed by Toshiba improve the indoor air quality benefits of this high-wall unit.

Key features

Enhanced aesthetics: with its slim design, the compact and stylish unit blends in with any room setting.

New enhanced filtration system: Zeolite Plus + Sasa filter to deodorise, Bio-Enzyme filter + Gingko filter to purify and new anti-oxidant Vitamin C filter.

Auto louvre mode: to allow optimum distribution of the air throughout the room.

TCC Link remote control (optional).

Wireless controller included.

R-410A HEAT PUMPS

STYLISH HIGH-WALL UNITS

Zeolite Plus filter

Bio Enzyme filter

Sasa filter
(virus deactivation)

Gingko filter
(allergy relieving)

Technical specifications heat pump

Indoor unit		SM562KRT-E SM56_AT-E	SM802KRT-E SM80_AT-E
Outdoor unit		2 HP	3 HP
Cooling capacity (min. – nom. – max.)	kW	1.5 – 5.0 – 5.6	1.5 – 6.7 – 7.0
EER	W/W	2.67	2.46
Heating capacity (min. – nom. – max.)	kW	1.5 – 5.6 – 6.3	1.5 – 8.0 – 9.0
COP	W/W	3.29	3.00
Energy efficiency class, cooling/heating		D/C	E/D
Sound pressure level (h/l)	dB(A)	39/33	45/36
Sound power level (h/l)	dB(A)	54/48	60/51
Dimensions (H × L × D)	mm	298 × 998 × 221	298 × 998 × 221
Weight	kg	12	12